



OLED HD DISPLAY

PROFESSIONAL FM TRANSCEIVER

**T-380**

- 2\*250 Memory Channels
- Single band standby or dual band standby selection
- One key create group, exit group;
- High/Low Power Selective 5W/1W
- Scrambler
- Bluetooth (optional)

## SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	UHF: 446~446.2MHz	RF Power	0.5W
Battery Capacity	2000mAh(Li-ion)	Modulate Mode (W/N)	16KΦF3E,11KΦF3E
Operating Temperature	-20°C~+60°C	Max. Freq. Deviation (W/N)	<5K / <2.5KHz
Frequency Combination	Phase lock frequency synthesize	Remain Wave Radiation	<-60dB
Frequency Stability	±2.5ppm	Transmitting Current	≤1300mA
Memory Channel	2×250 Channels	RECEIVE PART	
Working voltage	DC 7.4V	Sensitivity	<0.25μV(12dB SINAD)
Antenna Impedance	50Ω	Squelch Sensitivity	<0.20μV
Operating Mode	Simplex of co-frequency or alien frequency	Intermodulation Antijamming	50dB
Dimension	125mm×65mm×35mm	Audio Power output	500mW
Weight	150g (Include Battery Pack)	Receiving Current	≤100mA
		Squelch Standby	20mA

**ATLAS COMNET PVT. LTD.**

PLOT NO. 816, SECTOR-14, FARIDABAD, HARYANA-121007

Phone : 9213511631 | Tel : 0129-4019347

www.atlascomnet.com | www.atlascomnet.in

E-mail : sales@atlascomnet.net



 **Support**  
TYPE-C charger

# T-88



PROFESSIONAL FM TRANSCEIVER

Ultra Output Power Design  
Ultra Long Time Standby  
16 Memory Channels  
Sid Key Assignment

## SPECIFICATIONS

### GENERAL

Frequency Range	446-446.2 MHZ
Operating Temperature	-20°C-+60°C
Frequency Combination	Phase Lock frequency synthesizer
Frequency Stability	±2.5ppm
Memory Channel	16 Channels
Working Voltage	DC 3.7V
Antenna Impedance	50Ω
Operating Mode	Simplex of co-frequency or alien frequency
Dimension	125mm x 65 mm x 35mm
Weight	150g (Including Battery Pack)
Battery capacity	3000 mAh

### TRANSMIT PART

RF Power	0.5W
Modulate Mode [W/N]	16KΦF3E 11KΦF3E
Max. Freq. Deviation [W/N]	<5K/ <2.5KHz
Remain Wave Radiation	<-60dB
Transmitting Current	≤ 1300mA

### RECEIVE PART

Sensitivity	<0.25μV[12dB SINAD]
Squelch Sensitivity	<0.20μV
Intermodulation Antijamming	50dB
Audio Power Output	500mW
Receiving Current	≤100mA
Squelch Standby	20mA

## ATLAS COMNET PVT. LTD.

PLOT NO. 816, SECTOR-14, FARIDABAD, HARYANA-121007

Phone : 9213511631 | Tel : 0129-4019347

[www.atlascomnet.com](http://www.atlascomnet.com) | [www.atlascomnet.in](http://www.atlascomnet.in)

E-mail : [sales@atlascomnet.net](mailto:sales@atlascomnet.net)

# DELTA PLUS D66



## HIGH PERFORMANCE LF446 WALKY TALKY

### Main Functions

- 2400 mAh Li-ion battery
- CTCSS/DCS
- DCS Frequency Hopping
- VOX hands-free
- Scan
- 8 Groups Scrambler
- Voice Componder
- Busy channel lock
- Time out Timer



### General

### Receiver

### Transmitter

Frequency range	446-446.2Mhz	Sensitivity	≤0.30/0.20μV	RF power output	0.5W/5W
Channel capacity	16	Adjacent channel selectivity	60/70dB	Modulation type	F3E
Channel spacing	12.5/25.0KHz	Intermodulation	65dB	Spurious and Harmonic	-36dBm<1GHz;-30dBm>1GHz
Operating voltage	7.4V	Spurious response rejection	70dB	FM noise	45/40dB
Battery capacity	2400mAh (Li-ion)	Y/N	45/40dB	Audio distortion	≤5%
Battery duration (duty cycle 5-5-90)	about 20 hours	Audio power output	600mW	Modulation Limiting	±2.5KHz@12.5KHz; ±5.0KHz@25KHz
Frequency stability	±2.5ppm	Audio distortion	≤5%	Audio response	+1 to-3dB
Operating temperature	-20- +60°C				
Antenna impedance	50Ω				
Dimension (HxWxD) (without antenna)	113 x51 x 32mm				
Weight (with antenna and battery)	261g				

### Accessories



Battery Pack



Antenna



Charger



AC Adapter



Belt Clip



Hand Strap

CE RoHS

**ATLAS COMNET PVT. LTD.**

PLOT NO. 816, SECTOR-14, FARIDABAD, HARYANA-121007

Phone : 9213511631 | Tel : 0129-4019347

www.atlascomnet.com | www.atlascomnet.in

E-mail : sales@atlascomnet.net



Support  
TYPE-C charger

# T-88



PROFESSIONAL FM TRANSCEIVER  
Ultra Output Power Design  
Ultra Long Time Standby  
16 Memory Channels  
Sid Key Assignment

## SPECIFICATIONS

### GENERAL

Frequency Range	446-446.2 MHZ
Operating Temperature	-20°C-+60°C
Frequency Combination	Phase Lock frequency synthesizer
Frequency Stability	±2.5ppm
Memory Channel	16 Channels
Working Voltage	DC 3.7V
Antenna Impedance	50Ω
Operating Mode	Simplex of co-frequency or alien frequency
Dimension	125mm x 65 mm x 35mm
Weight	150g (Including Battery Pack)
Battery capacity	3000 mAh

### TRANSMIT PART

RF Power	0.5W
Modulate Mode [W/N]	16KΦF3E 11KΦF3E
Max. Freq. Deviation [W/N]	<5K/ <2.5KHz
Remain Wave Radiation	<-60dB
Transmitting Current	≤ 1300mA

### RECEIVE PART

Sensitivity	<0.25μV[12dB SINAD]
Squelch Sensitivity	<0.20μV
Intermodulation Antijamming	50dB
Audio Power Output	500mW
Receiving Current	≤100mA
Squelch Standby	20mA

## ATLAS COMNET PVT. LTD.

PLOT NO. 816, SECTOR-14, FARIDABAD, HARYANA-121007

Phone : 9213511631 | Tel : 0129-4019347

www.atlascomnet.com | www.atlascomnet.in

E-mail : sales@atlascomnet.net